

Bevelling system B15 AIR

Maximum bevel width 15 mm / 0.6 in. Edge rounding function.

B15 Air Powerful 2984 W pneumatic engine











Art. Nr. 27220

Heavy-duty design








Thousands of satisfied customers throughout the world









Designed for bevelling and deburring of straight and shaped parts, internal and external radiuses and holes. Specially designed for producing visual bevels and welding preparation. Powerful pneumatic drive for extreme loads.

- Scale for accurate bevel size adjustment.
- For bevelling and deburring of steel, aluminium and other materials.
- Replaceable head for changing bevel angle.
- Powerful handheld equipment.
- Also suitable for explosion-risk operations.
- Edge rounding function, preparation before surface treatment.

Technical data:

Bevel angle:	Replaceable head 30°, 37,5°, 45°, 50°, 60°- other angles on demand
Bevel width:	0 to 15 mm / 0 to 0.06 in < 400 MPa / 58 015 PSI
	0 to 8 mm / 0 to 0.31 in > 400 MPa / 58 015 PSI
Engine:	Pneumatic
Engine Power:	2984 W
Speed:	6000 rpm
Air consumption:	750 l/min
Operating pressure:	6 bar / 87.02 PSI
Weight:	7,5 kg / 16.5 lb
Number of cutting inserts:	6 pcs

Included in price:

B15 AIR bevelling and deburring system (without the head). Tools for an operators. Packed in a cardboard. User manual.

Machine name:	Art. Nr.
Bevelling and deburring system B15 AIR	27220

Accessories:	Art. Nr.
30° cutting head (including inserts, screws, bolts and roller). Guide roller diameter Ø 34 mm / 1.34 in	
37.5° cutting head (including inserts, screws, bolts and roller). Guide roller diameter Ø 28 mm / 1.10 in	
45° cutting head (including inserts, screws, bolts and roller). Guide roller diameter Ø 28 mm / 1.10 in	
50° cutting head (including inserts, screws, bolts and roller). Guide roller diameter Ø 28 mm / 1.10 in	
60° cutting head (including inserts, screws, bolts and roller). Guide roller diameter Ø 27 mm / 1.06 in	
Cutting head with non-standard angle. (Including inserts, screws, bolts and roller)	
Coated cutting inserts - four-sided (pack of 10 pcs)	
Edge rounding cutter R2.5 mm / 0.08 in (including inserts, screws, bolts and roller). Guide roller diameter Ø 41 mm / 1.61 in	
Edge rounding cutter R3.5 mm / 0.12 in (including inserts, screws, bolts and roller). Guide roller diameter Ø 40 mm / 1.57 in	
Cutting inserts for rounding edges R2.5 mm / 0.08 in (pack of 10 pcs)	
Cutting inserts for rounding edges R3.5 mm / 0.12 in (pack of 10 pcs)	
Cutting inserts for rounding edges R4mm / 0.16 in (pack of 10 pcs). Compatible with head R3.5 mm / 0.12 in	
Screw for the inserts	
Pneumatic set (air filtration, lubrication and air pressure control unit, 10 m pressure hose including the respective couplings)	
Screw for the radius / rounding inserts	
Screw for the impeler / guiding roll	



Production and development in EU